

## 2009 Class Rules 2.8 Turbo Diesel Truck

8500-pound maximum weight.

DOT street legal tires. No chains, cut tires, or studs. 35" Maximum diameter. Single or Dual wheels are allowed.

Manufactured style flat bed or factory bed (no thin covering fenders).

Weight bracket must be fastened to both sides of frame support.

Must have an air shutoff.

2.8 Turbo size no bushings allowed.

Hitch: The hitch must be a receiver-style hitch; reinforcements are permitted. Reinforcements must not extend forward of the centerline of the rear axle tube. Trick hitches are prohibited. The hooking point must be the rear most point on the vehicle and must be rearward of the stock location of the tailgate. The must be horizontal to the ground and stationary in all directions. Bumpers may be notched or removed. The hitch height from the ground must not exceed 26 inches. The hooking point must have a minimum opening of 3.00 inches inside diameter for sled hook. The hitch height will be measured to top of clevis loop

No alcohol, nitrous oxide, or propane injection.

Engine must be derived stock from the factory in a one-ton pickup truck or less application. Engine does not have to be the same manufacturer as the truck. For example: a Cummins engine may be transplanted in a Ford or Chevy truck.

Front hanging weights are allowed, but not to exceed 60 inches forward of the center of the front axle.

Drive train must be OEM from one ton or less pickup truck. For example: no drop boxes or reversers.

Rear suspension may be blocked. Blocks must be easily removed and no solid suspensions.

Trucks with manual transmissions, running in excess of 4000 rpm's, must run a scatter proof blanket on the bell housing.

3/8" bolts must be through the exhaust in a cross pattern as close to the turbocharger as possible.

Axle bolts must be covered.

Must have U-joint shields at least 6" long around rear U-joint.

All trucks must have fuel shutoffs; kill switches, driveline loops, and a fire extinguisher. Exhaust must go up or down only.

5lb. Fire Extinguisher mandatory