

11000 LB PRO FIELD TRACTOR

1. 20.8-38 max. tire size
2. No cut tires
3. Diesel only. No alcohol, nitrous or propane.
4. Water Injection permitted ...(water only no additives)
5. Roll cage or OEM factory roll bar mandatory.
6. Kill switch. Air Shut (MANDATORY)
7. 2 ½ turbo inlet, close to turbo fan. No slugs or modification to inlet housing , Map enhancements permitted . Turbos will be checked with a 2.55 inch plug.
8. 20 inch hitch height , must be stationary in all 4 directions with a minimum of 3" opening for sled hook.
9. Each tractor is to look standard for its year and model in appearance. All major factory sheet metals are and must comply with make and model. Bubbles will be allowed to accommodate aftermarket turbo that were made for the make and model in that series of tractor. Frame, transmission, rear-end, and fuel system must comply with model of tractor. Parts such as M&W turbo chargers and oil pans are allowed, but must be the one designed for the model of tractor they are in use on. Gear ratios in transmission may be changed.
10. Steel hubs only- No cast iron, cast steel OK
11. Electric fan or 60 thousandths around fan.
12. Seat belts and helmets required if have a roll cage .
13. No third arm Hitches
14. Dead man throttles mandatory.
15. No weights beyond 24" most forward point of tractor.
16. Must run OEM intake and exhaust
17. Mandatory wheelie bars-Must have 5x5" padded no more than 10 inches from ground. Must be three inch from farthest point of the tire to the front of pad.

18. One driver per tractor per class
19. No third arm weight bracket. Must be stationary on tractor
20. 3000 RPMS Max- All tractors must have functioning RPM plug on rear of tractor so that it can be plugged into sled , dummy plugs with not be tolerated and subject to disciplinary action by the Executive Committee.
21. Driver must remain seated with one hand on the steering at all times. Tractor must be operated in a safe manner at all times or the driver and the tractor will be disqualified. Excessive wheelie height will be red flagged at flagmen's discretion.
22. 2wd drive tractors only no duals.
23. Engines limited to 470 cubic inch on 6 cylinder engines, and 540 on 8 cylinder engines.
24. Engines are subject to be pumped or teched my other procedures to determine proper cubic inch displacement at any time.
25. Clutch Scatter Blankets or Steel Shields are recommended .